

Verhoudingstabel HF S-punten / dBuV / Volt / dBm

HF S-punt	dBuV	uV / mV over 50 ohm	dBm
	-15	0,178 uV	-122
1	-14	0,2 uV	-121
	-13	0,224 uV	-120
	-10	0,316 uV	-117
2	-8	0,4 uV	-115
	-5	0,562 uV	-112
	-3	0,707 uV	-110
3	-2	0,8 uV	-109
	0	1 uV	-107
	2	1,26 uV	-105
4	4	1,585 uV	-103
	5	1,776 uV	-102
	7	2,24 uV	-100
5	10	3,16 uV	-97
	12	3,98 uV	-95
	15	5,6 uV	-92
6	16	6,3 uV	-91
	17	7,07 uV	-90
	20	10,0 uV	-87
7	22	12,6 uV	-85
	25	17,76 uV	-82
	27	22,4 uV	-80
8	28	25 uV	-79
	30	31,6 uV	-77
	32	39,8 uV	-75
9	34	50 uV	-73
	35	56,2 uV	-72
	37	70,7 uV	-70
	40	100 uV	-67
	42	125,7 uV	-65
9 + 10 dB	44	158,5 uV	-63
	45	177,6 uV	-62
	47	224 uV	-60
	50	316 uV	-57
	52	398 uV	-55
9 + 20 dB	54	500 uV	-53
	55	561,7 uV	-52
	57	707 uV	-50
	60	1000 uV / 1 mV	-47
	62	1,26 mV	-45
9 + 30 dB	64	1,58 mV	-43
	65	1,78 mV	-42
	67	2,24 mV	-40
	70	3,16 mV	-37
	72	3,98 mV	-35
9 + 40 dB	74	5,0 mV	-33
	75	5,62 mV	-32
	77	7,07 mV	-30
	80	10 mV	-27
	82	12,6 mV	-25
9 + 50 dB	84	15,85 mV	-23
	85	17,76 mV	-22
	87	22,36 mV	-20
	90	31,6 mV	-17
	92	39,76 mV	-15
9 + 60 dB	94	50 mV	-13
	95	56,17 mV	-12
	96	63 mV	-11
	97	70,7 mV	-10
	100	100 mV	-7