

Verhoudingstabel HF S-punten / dBuV / dBmV / Volt / dBm

HF S-punt	dBuV	dBmV	uV / mV over 50 ohm	dBm
	-15	-75	0,178 uV	-122
1	-14	-74	0,2 uV	-121
	-13	-73	0,224 uV	-120
	-10	-70	0,316 uV	-117
2	-8	-68	0,4 uV	-115
	-5	-65	0,562 uV	-112
	-3	-63	0,707 uV	-110
3	-2	-62	0,8 uV	-109
	0	-60	1 uV	-107
	2	-58	1,26 uV	-105
4	4	-56	1,585 uV	-103
	5	-55	1,776 uV	-102
	7	-53	2,24 uV	-100
5	10	-50	3,16 uV	-97
	12	-48	3,98 uV	-95
	15	-45	5,6 uV	-92
6	16	-44	6,3 uV	-91
	17	-43	7,07 uV	-90
	20	-40	10,0 uV	-87
7	22	-38	12,6 uV	-85
	25	-35	17,76 uV	-82
	27	-33	22,4 uV	-80
8	28	-32	25 uV	-79
	30	-30	31,6 uV	-77
	32	-28	39,8 uV	-75
9	34	-26	50 uV	-73
	35	-25	56,2 uV	-72
	37	-23	70,7 uV	-70
	40	-20	100 uV	-67
	42	-18	125,7 uV	-65
9 + 10 dB	44	-16	158,5 uV	-63
	45	-15	177,6 uV	-62
	47	-13	224 uV	-60
	50	-10	316 uV	-57
	52	-8	398 uV	-55
9 + 20 dB	54	-6	500 uV	-53
	55	-5	561,7 uV	-52
	57	-3	707 uV	-50
	60	0	1000 uV / 1 mV	-47
	62	2	1,26 mV	-45
9 + 30 dB	64	4	1,58 mV	-43
	65	5	1,78 mV	-42
	67	7	2,24 mV	-40
	70	10	3,16 mV	-37
	72	12	3,98 mV	-35
9 + 40 dB	74	14	5,0 mV	-33
	75	15	5,62 mV	-32
	77	17	7,07 mV	-30
	80	20	10 mV	-27
	82	22	12,6 mV	-25
9 + 50 dB	84	24	15,85 mV	-23
	85	25	17,76 mV	-22
	87	27	22,36 mV	-20
	90	30	31,6 mV	-17
	92	32	39,76 mV	-15
9 + 60 dB	94	34	50 mV	-13
	95	35	56,17 mV	-12
	96	36	63 mV	-11
	97	37	70,7 mV	-10
	100	40	100 mV	-7
	102	42	126 mV	-5
9 + 70 dB	104	44	158,5 mV	-3
	105	45	177,6 mV	-2
	107	47	223,6 mV	0
	110	50	316 mV	3
	112	52	397,6 mV	5
9 + 80 dB	114	54	500 mV	7
	115	55	561,7 mV	8
	116	56	630 mV	9
	117	57	707 mV	10
	120	60	1000 mV / 1V	13
	122	62	1,26 V	15
9 + 90 dB	124	64	1,585 V	17
	125	65	1,776 V	18
	127	67	2,236 V	20