

MMIC bijzonderheden / eigenschappen

standaard altijd 50 Ohm

type	gain dB	power dBm	R1 b-gnd	R2 c-b	Rtot c-gnd	Uc V	Ic mA	12V-R Ohm	code of bijz.
MSA0235 idem	12	4,5	194 193	373 373	572 560	5	25	280	A02
MAR3 MAR3 ouder ander	12	10	194 182 180	354 330 326	547 511 506	5	35	200	A03 oranje oranje
MSA385 MAV3	12 12	10 10	164 168	317 304	480 472	5 5	35 35	200 200	A03 3
MSA0435 MAR4	8,5 8	12,5 12,5	118 135	229 253	345 387	5,25 5,25	50 50	150	A04 A04 wit-geel
ERA4	14	17,3	300	250	550	4,5 /5	65	110	E4
MSA0520	8,5	23	865	2173	3037	12 !	165	xxx koelen	hogere U, min 15 - 18V PSU
GALI-5+ GALI-51	20 18	18 18	1117 851	632 441	1810 1292	4,4 4,4	65 65	110 110	05 51
MAR6 MSA0686	21 18,5	3 2	540 480	677 605	1215 1083	3,5 3,5	16 16	560 560	A06 wit A06
MAR8 MSA0885 MSA0886 ?idem	28 22-30 22,5	12,5 12,5 12,5	2628 1617 1613 1742	9900 7020 6950 5607	12520 8650 8580 7340	7,8 7,8 7,8 7,8	36 36 36 36	120 120 120 120	A08 blauw A08 A08 A81
INA02184 INA02186	31	11	6,435k	38k	37k?	5,5	35	180	N02 N02
INA10386 INA10386	26 26	10 10	657 828	6,62M? 31,5k	6,68M? 39,5k	6 6	40 45		mark-103 mark-N10
MAV11	12	17,5	2802	4670	7480	5,5	60	120	A
INA03184	25	-2	1,422k	7,2M	7,2M	4	10	800	mark-N03
SGA-3486 SGA-1263	18 15	12,7 -7,8	1095 R32= 2570	772 X	1805 R64= 72	2,9 2,8	35 8	270 270 Vcc=5	A34 or 34Z very small signal A12